

---

# Santovac<sup>®</sup> Fluids

## Material Safety Data Sheet

Page 1 of 6

---

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

PRODUCT NAME: **ACCL-7 CONNECTOR LUBRICANT**

Date: 01/03/00

**Chemical Family:** Aliphatic Hydrocarbon/Polyphenyl Ether

**Chemical Name:** Synthetic Isoparaffinic Hydrocarbon/Polyphenyl Ether

SANTOVAC<sup>®</sup> FLUIDS, INC., 8 Governor Drive, St. Charles, MO 63301

FOR CHEMICAL EMERGENCY, SPILL LEAK, FIRE EXPOSURE, OR ACCIDENT  
Call CHEMTREC – Day or Night – 1-800-424-9300. Toll free in the continental  
U.S., Hawaii, Puerto Rico, Canada, Alaska, or Virgin Islands. For calls originating  
elsewhere: 703-527-3887 (collect calls accepted).

For additional non-emergency information, call: 636-723-0240

---

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

---

Near colorless liquid with a faint purple hue

Note: ACCL-7 Connector Lubricant is a proprietary blend manufactured by  
Santovac Fluids, Inc. All components appear on the Inventory of Chemical  
Substances published by the U.S. Environmental Protection Agency (EPA) under  
authority of the Toxic Substances Control Act (TSCA).

---

### 3. HAZARDS IDENTIFICATION

---

This product is hazardous as defined in CFR 1910.1200.

OSHA HAZARD

COMBUSTIBLE

POTENTIAL HEALTH EFFECTS

EYE CONTACT:

Slightly irritating but does not injure eye tissue.

SKIN CONTACT:

Frequent or prolonged contact may irritate and cause dermatitis.

Low order of toxicity.

Skin contact may aggravate an existing dermatitis condition.

INHALATION:

High vapor/aerosol concentrations (greater than approximately 1000 ppm) are  
irritating to the eyes and the respiratory tract, may cause headaches, dizziness,

anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

**INGESTION:**

Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death. Minimal toxicity.

---

**4. FIRST AID MEASURES**

---

**EYE CONTACT:**

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

**SKIN CONTACT:**

Flush with large amounts of water; use soap if available.

Remove grossly contaminated clothing, including shoes, and launder before reuse.

**INHALATION:**

Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

**INGESTION:**

If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

---

**5. FIRE FIGHTING MEASURES**

---

**FLASHPOINT:** 120°F.    **Method:** TCC    **NOTE:** Minimum

**FLAMMABLE LIMITS:**    **LEL:** 1.3    **UEL:** 9.8 @ 77°F. **NOTE:** Approximate

**AUTOIGNITION TEMPERATURE:** 660°F. **NOTE:** Approximate

**GENERAL HAZARD:** Combustible Liquids can form combustible mixtures at temperatures at or above the flashpoint. Material can accumulate and discharge static charges, which can cause an incendiary electrical discharge.

“Empty” containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC

ELECTRICITY OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### LAND SPILL

Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without hazard. For small spills implement cleanup procedures; for large spills, implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 REGULATORY INFORMATION) notify the National Response Center. Prevent liquid from entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust. Recover by pumping (use an explosion-proof or hand pump) or with a suitable absorbent. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

### WATER SPILL

Eliminate sources of ignition. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazards and request all to stay clear. Remove from surface by skimming or with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

---

## 7. HANDLING AND STORAGE

---

### ELECTROSTATIC ACCUMULATION HAZARD:

Yes, use proper grounding procedure

STORAGE TEMPERATURE, °F: Ambient

STORAGE/TRANSPORT PRESSURE, mm. Hg.: Atmospheric

LOADING/UNLOADING TEMPERATURE, °F: Ambient

LOADING/UNLOADING VISCOSITY, cSt: Approximately 2.1

### STORAGE AND HANDLING:

Keep container closed. Handle and open containers with care. Store in a cool, well-ventilated place away from incompatible materials. Do NOT handle or store near an open flame, heat or other sources of ignition. Protect material from direct sunlight. Material will accumulate static charges, which may cause an electrical spark (ignition source). Use proper grounding procedures.

DO NOT pressurize, cut, heat, or weld containers. Empty product containers may contain product residue. DO NOT reuse empty containers without commercial cleaning or reconditioning.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### EXPOSURE CONTROLS

The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

### PERSONAL PROTECTION

For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where contact may occur, wear safety glasses with side shields.

Where concentrations in air may exceed the limits given in this section and engineering, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

### RECOMMENDED OCCUPATIONAL EXPOSURE LIMIT

300 ppm total hydrocarbon

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

SPECIFIC GRAVITY:	0.77 @ 60°F
VAPOR PRESSURE:	1 mm. Hg. @ 68°F 3 mm. Hg. @ 100°F (approximate)
SOLUBILITY IN WATER:	<0.01%w @ 77°F
VISCOSITY OF LIQUID:	1.7 cSt @ 77°F
SPECIFIC GRAVITY (VAPOR):	5.40 calculated @ 1 atm (air = 1)
FREEZING/MELTING POINT:	<-76°F
EVAPORATION RATE:	<0.1 (n-butyl acetate = 1)
BOILING POINT:	354-372°F

---

## 10. STABILITY AND REACTIVITY

---

STABILITY: Stable

CONDITIONS TO AVOID: Not Applicable

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID HAZARDOUS POLYMERIZATION: Not Applicable

MATERIALS TO AVOID INCOMPATIBILITY: Strong Oxidizing Agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

---

## 11. TOXICOLOGICAL INFORMATION

---

Please refer to Section 3 for available information on potential health effects.

---

## 12. ECOLOGICAL INFORMATION

---

No specific ecological data are available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

---

## 13. DISPOSAL CONSIDERATIONS

---

This material when discarded is a hazardous waste as defined by the Resource, Conservation and Recovery Act (RCRA), 40 CFR 261. Dispose of in accordance with all federal, state and local environmental regulations. Recommended method of disposal is by high temperature incineration at a RCRA approved TSD. If there are any questions regarding the disposal of this material, please consult the Environmental, Health & Safety Department of Santovac Fluids, Inc. at 636-946-2355.

---

## 14. TRANSPORT INFORMATION

---

### DEPARTMENT OF TRANSPORTATION (DOT):

#### DOT SHIPPING DESCRIPTION:

PETROLEUM DISTILLATE, n.o.s., COMBUSTIBLE LIQUID, UN1268, III

NOTE: In containers of 119 gallons or less this product is not regulated by DOT.

---

## 15. REGULATORY INFORMATION

---

### CLEAN WATER ACT/OIL POLLUTION ACT:

This product is classified as an oil under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Act of 1990. Discharge or spills which produce a visible sheen on either surface water, or in waterways/sewers which lead to surface water, must be reported to the National Response Center at 800-424-8802.

### CERCLA:

If this product is accidentally spilled, it is not subject to any special reporting under the requirements of the Comprehensive Environmental response, Compensation, and Liability Act (CERCLA). We recommend you contact local authorities to determine if there may be other local reporting requirements.

**SANTOVAC® MATERIAL SAFETY DATA SHEET  
ACCL-7 CONNECTOR LUBRICANT**

SARA TITLE III:

Under the provisions of Title III, Sections 311/312 of the Superfund Amendments and Reauthorization Act, this product is classified into the following hazard categories: FIRE.

This information may be subject to the provisions of the Community Right-To-Know Reporting Requirements (40 CFR 370) if threshold quantity criteria are met.

---

16. OTHER INFORMATION

---

HAZARD RATING SYSTEMS:

This is for people trained in:

National Paint & Coatings Association's (NPCA) Hazardous Materials Identification System (HMIS) and National Fire Protection Association (NFPA 704):

	<u>NPCA-HMIS</u>	<u>NFPA 704</u>	<u>KEY</u>
HEALTH	1	1	4 = Severe
FLAMMABILITY	2	2	3 = Serious
REACTIVITY	0	0	2 = Moderate 1 = Slight 0 = Minimal

Revision No.: 1

Reason for revision: Section 13; update disposal language

---

NOTICE: Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, Santovac® Fluids, Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied upon the conditions that the persons receiving same will make their own determinations as to its suitability for their purposes prior to use. In no event will Santovac® Fluids, Inc. be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OR MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

---

Date 01/11/202

Supersedes : 01/03/00